		Key features
		 Live view, recording&playback up to 12 MP resolution Up to 16 channel IP cameras can be connected with built-in PoE inputs Advanced H.265+ Video Compression
		• Supports iPhone、 iPad、 Android mobile remote monitoring
		· Connectable to the third-party network cameras
		· HDMI Video output at up to 4K (3840 × 2160) resolution
		\cdot 2 SATA interfaces connectable for recording and backup
		Annke Vision for easy remote view
		Support 4-ch Human and vehicle targets detection
Model Number		N46PCK
		NVR
Video & Audio	Video Compression	H.264+/H.264/H.265/H.265+
	IP Video Input	16CH PoE
	Video Output	HDMI up to 4K, VGA up to 1080p
	Audio Input/Output	1/1 RCA
	Incoming/Outgoing Bandwidth	160/80 M
	Max. Recording Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)
	Max. Playback Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)
	, Max. Playback Channel	16СН
	Max. Playback Capacity	1-ch@12 MP(4096 X 3072) (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps)
Hard Drive	HDD	2 SATA Interface
	HDD Capacity	Up to 8 TB Capacity for each disk
External Interface	Network Interface	RJ45 X1 (10/100/M)
	РоЕ	16, RJ-45 10/100 Mbps self-adaptive Ethernet interface, IEEE 802.3 af/at
	USB	2X USB 2.0
Smart Function	Deep learning	16-ch Human and vehicle targets detection(Need IP camera support)
		4-ch Human and vehicle targets detection(IP camera does not need to support this function but the resolution cannot exceed 4MP)
	Smart Event	Line crossing detection, intrusion detection, region entrance detection, region exiting detection(Need IP camera support)
General	Operating Power	AC 100-240 V
	Power Consumption	\leqslant 15 W (Without HDD and PoE)
		PoE: Max. 25.5W for Single Port
	Working Temperature	14 °F — 131 °F/-10 °C — 55 °C
	Dimensions (W X H X D)	15.2" X 12.4" X 2.0"/385 X 315 X 52 mm
	Weight (Without Hard Disk)	6.6 lbs./3 kg
Packaging Contents		
	NVR	1
USB Mouse		1
Power Cable		1
1M network cable		1
1.8M HDMI cable		1
	User's Manual For NVR	1